

KAFO CNC freesmachine VMM 21100



Item	VMM-21100	Rapid traverse(X,Y axis)	12000,12000 (472ipm)
Table size overall	2400x1100mm	Rapid traverse(Z axis)	10,000mm/min (394ipm)
T-slot(WxNoxSlots)	22mmx7x150mm (0.866"x0.28x5.91")	Feed rates(X,Y,Z axis)	4000mm/min (157ipm)
Table load capacity	3000kgs (6600lbs)	Feed motors	AC 3.3/3.3/3.3KW (AC4.4/4.4/4.4HP)
X .Y .Z axis travel	2150(85"),1000(33.5") (39.4"*) ,790(31.5") mm	Spindle motor(Cont./30min)	AC 11/15KW (AC15/20HP)
Spindle nose to table	250-1040mm (9.8"-41")	Spindle head coolant	AC 0.4KW-4P (AC1/2HP-4P)
Spindle center to column	1042mm	Automatic slideway lubricant	AC 60W-4P (AC 1/12HP-4P)
Spindle taper	BT-50(CAT50)	Coolant pump	AC-0.4KW-4P (AC 1/2HP-4P)
Pull stud	MAS-BT-50/P50-T	Hydraulic unit	AC 2.2KW-4P (AC 3HP-4P)
Spindle speed Gear	4000rpm(6000rpm/8000rpm)	Floor area(LxW)	5900x3500mm (232.28"x137.80")
Belt	6000rpm(8000rpm)	Machine overall size(LxWxH)	5900x3500x3510mm (232.28"x137.80x138.19")
Change of speeds	Infinitely variable (2 setps)	Net weight	16000kgs(37400lbs)